

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P313	Get medical advice/attention.
P501	Dispose of contents/container to ...

Supplementary Precautionary Statements

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash ... thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P337	If eye irritation persists:
P403+233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P410+412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

Supplemental Label Information

EUH066	Repeated exposure may cause skin dryness or cracking.
--------	---

2.3. Other hazards

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

ACETONE		30-60%
CAS-No.: 67-64-1	EC No.: 200-662-2	
Classification (EC 1272/2008) Flam. Liq. 2 - H225 EUH066 Eye Irrit. 2 - H319 STOT Single 3 - H336	Classification (67/548) F;R11 Xi;R36 R66 R67	
BUTANONE		10-30%
CAS-No.: 78-93-3	EC No.: 201-159-0	
Classification (EC 1272/2008) Flam. Liq. 2 - H225 EUH066 Eye Irrit. 2 - H319 STOT Single 3 - H336	Classification (67/548) F;R11 Xi;R36 R66 R67	
BUTYL ACETATE -norm		1-5%
CAS-No.: 123-86-4	EC No.: 204-658-1	
Classification (EC 1272/2008) Flam. Liq. 3 - H226 EUH066 STOT Single 3 - H336	Classification (67/548) R10 R66 R67	
DIMETHYL ETHER		30-60%
CAS-No.: 115-10-6	EC No.: 204-065-8	
Classification (EC 1272/2008) Flam. Gas 1 - H220	Classification (67/548) F+;R12	

ETHANOL		1-5%
CAS-No.: 64-17-5		EC No.: 200-578-6
Classification (EC 1272/2008) Flam. Liq. 2 - H225	Classification (67/548) F;R11	
ISOBUTYL ACETATE		1-5%
CAS-No.: 110-19-0		EC No.: 203-745-1
Classification (EC 1272/2008) Flam. Liq. 2 - H225 EUH066	Classification (67/548) F;R11 R66	
PROPAN-1-OL		1-5%
CAS-No.: 71-23-8		EC No.: 200-746-9
Classification (EC 1272/2008) Flam. Liq. 2 - H225 Eye Dam. 1 - H318 STOT Single 3 - H336	Classification (67/548) F;R11 Xi;R41 R67	
TOLUENE		1-5%
CAS-No.: 108-88-3		EC No.: 203-625-9
Classification (EC 1272/2008) Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Repr. 2 - H361d STOT Single 3 - H336 STOT Rep. 2 - H373 Asp. Tox. 1 - H304	Classification (67/548) F;R11 Repr.Cat.3;R63 Xn;R48/20,R65 Xi;R38 R67	
XYLENE		1-5%
CAS-No.: 1330-20-7		EC No.: 215-535-7
Classification (EC 1272/2008) Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315	Classification (67/548) R10 Xn;R20/21 Xi;R38	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Information

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

Inhalation.

Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep the affected person warm and at rest. Get prompt medical attention.

Ingestion

Get medical attention.

Skin Contact

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

Eye Contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing Media

Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

5.2. Special hazards arising from the substance or mixture

Unusual Fire & Explosion Hazards

Aerosol cans may explode in a fire.

5.3. Advice for firefighters

Special Fire Fighting Procedures

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Let evaporate. Keep out of confined spaces because of explosion risk. If leakage cannot be stopped, evacuate area.

6.4. Reference to other sections

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

7.2. Conditions for safe storage, including any incompatibilities

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

7.3. Specific end use(s)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
ACETONE	WEL	500 ppm	1210 mg/m3	1500 ppm	3620 mg/m3	
BUTANONE	WEL	200 ppm(Sk)	600 mg/m3(Sk)	300 ppm(Sk)	899 mg/m3(Sk)	
BUTYL ACETATE -norm	WEL	150 ppm	724 mg/m3	200 ppm	966 mg/m3	
DIMETHYL ETHER	WEL	400 ppm	766 mg/m3	500 ppm	958 mg/m3	
ETHANOL	WEL	1000 ppm	1920 mg/m3			
ISOBUTYL ACETATE	WEL	150 ppm	724 mg/m3	187 ppm	903 mg/m3	
PROPAN-1-OL	WEL	200 ppm(Sk)	500 mg/m3(Sk)	250 ppm(Sk)	625 mg/m3(Sk)	
TOLUENE	WEL	50 ppm(Sk)	191 mg/m3(Sk)	150 ppm(Sk)	574 mg/m3(Sk)	
XYLENE	WEL	50 ppm(Sk)	220 mg/m3(Sk)	100 ppm(Sk)	441 mg/m3(Sk)	

WEL = Workplace Exposure Limit.

Ingredient Comments

WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective Equipment



Engineering Measures

Provide adequate general and local exhaust ventilation.

Respiratory Equipment

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit.

Hand Protection

Use protective gloves.

Eye Protection

Use eye protection.

Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene Measures

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance	Aerosol
Colour	Misc. colours Colourless to pale yellow
Flash Point (°C)	-40
Auto Ignition Temperature (°C)	350
Flammability Limit - Lower(%)	3.4
Flammability Limit - Upper(%)	18

9.2. Other information

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

10.2. Chemical stability

Stable under normal temperature conditions.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Other Health Effects

Carcinogen Category 3.

Health Warnings

INHALATION. May cause irritation to the respiratory system. Solvent vapours are hazardous and may cause nausea, sickness and headaches. Prolonged inhalation of high concentrations may damage respiratory system. SKIN CONTACT. Product has a defatting effect on skin. May cause skin irritation/eczema. EYE CONTACT. Irritating to eyes.

Route of entry

Inhalation.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity:

Not regarded as dangerous for the environment.

12.1. Toxicity

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.

SECTION 14: TRANSPORT INFORMATION

14.1. UN number

UN No. (ADR/RID/ADN)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950

14.2 UN Proper Shipping Name

Proper Shipping Name AEROSOLS, FLAMMABLE, NOS

14.3 Transport hazard class(es)

ADR/RID/ADN Class	2.1
ADR/RID/ADN Class	Class 2.1: Flammable gases.
ADR Label No.	2.1
IMDG Class	9
ICAO Class/Division	2.1
ICAO Subsidiary risk	N/A

Transport Labels



14.4. Packing group

ADR/RID/ADN Packing group	10(b)2
IMDG Packing group	N/A
ICAO Packing group	N/A

14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant
No.

14.6. Special precautions for user

EMS	2-13
Emergency Action Code	N/A

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Uk Regulatory References

Petroleum (Consolidation) Act, as amended 1984 SI 1244. Highly Flammable Liquid Regulations 1972.

Environmental Listing

Rivers (Prevention of Pollution) Act 1961. Control of Pollution (Special Waste Regulations) Act 1980.

Approved Code Of Practice

Classification and Labelling of Substances and Preparations Dangerous for Supply.

Guidance Notes

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

Eu Legislation

System of specific information relating to Dangerous Preparations. 2001/58/EC.

15.2. Chemical Safety Assessment

SECTION 16: OTHER INFORMATION

Risk Phrases In Full

R10	Flammable.
R11	Highly flammable.
R12	Extremely flammable.
R20/21	Harmful by inhalation and in contact with skin.
R36	Irritating to eyes.
R38	Irritating to skin.
R41	Risk of serious damage to eyes.
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R63	Possible risk of harm to the unborn child.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

Hazard Statements In Full

EUH066	Repeated exposure may cause skin dryness or cracking.
H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs <<Organs>> through prolonged or repeated exposure.